

(12) **United States Patent**
Hiraoka

(10) **Patent No.:** **US 8,676,278 B2**
(45) **Date of Patent:** **Mar. 18, 2014**

(54) **MOBILE TERMINAL DEVICE**

(56) **References Cited**

(75) Inventor: **Michiaki Hiraoka**, Yokohama (JP)

U.S. PATENT DOCUMENTS

(73) Assignee: **Kyocera Corporation**, Kyoto (JP)

6,529,742 B1 * 3/2003 Yang 455/556.1
6,646,626 B1 * 11/2003 Uskali et al. 345/87
6,728,557 B1 * 4/2004 Tracy et al. 455/575.3
7,000,289 B2 * 2/2006 Cedrone 16/309
7,483,723 B2 * 1/2009 Soderlund 455/575.1
7,603,143 B2 * 10/2009 Kang et al. 455/566
2004/0097262 A1 * 5/2004 Lee 455/556.1

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 705 days.

(Continued)

(21) Appl. No.: **12/280,937**

FOREIGN PATENT DOCUMENTS

(22) PCT Filed: **Feb. 21, 2007**

(86) PCT No.: **PCT/JP2007/053205**

JP 2002009920 A 1/2002
JP 2002101171 A 4/2002

§ 371 (c)(1),

(Continued)

(2), (4) Date: **Jun. 23, 2009**

OTHER PUBLICATIONS

(87) PCT Pub. No.: **WO2007/097369**

International Search Report for corresponding PCT application PCT/JP2007/053205 lists the references above.

PCT Pub. Date: **Aug. 30, 2007**

(65) **Prior Publication Data**

Primary Examiner — San Htun

US 2009/0318195 A1 Dec. 24, 2009

(74) *Attorney, Agent, or Firm* — DLA Piper LLP (US)

(30) **Foreign Application Priority Data**

(57) **ABSTRACT**

Feb. 27, 2006 (JP) 2006-050287

(51) **Int. Cl.**

H04M 1/00 (2006.01)

(52) **U.S. Cl.**

USPC **455/575.3**; 455/575.1; 455/575.4

(58) **Field of Classification Search**

USPC 455/575.1–575.9, 344–350, 90.3, 455/550.1, 556.1, 556.2, 557; 16/312, 309; 345/169; 361/600, 625, 361/679.01–679.09, 679.1, 679.11–679.19, 361/679.2, 679.21–679.29, 679.3, 361/679.31–679.39, 679.4, 679.41–679.44

See application file for complete search history.

A mobile terminal device comprise a first housing **11a** provided with a displaying unit **13**; a second housing **11b** on which the first housing **11a** is laid; a hinge portion **12** pivotably connecting respective one end portions of the first housing **11a** and second housing **11b** with each other such that the first housing **11a** moves toward/away from the second housing **11b**; and a self-stand maintaining unit for maintaining a self-standing state where the displaying unit **13** is inclined by pivoting the first housing **11a** relative to the second housing **11b** with the hinge portion **12** as a pivoting center, as well as moving the first housing **11a** along an axial direction of the hinge **12** to bring a side of the first housing **11a** and a contact portion **A** on a side surface of the second housing **11b** into contact with a placement surface.

9 Claims, 12 Drawing Sheets

